

LIVEO-530 PBK

5.25" Waterproof 2-way Passive Wall-Mount Speaker Pair, Black

Liveo series combines simplicity and elegance with sturdiness and ease of installation. Whether outdoor or indoor, low-impedance or constant-voltage line, Liveo guarantees the right solution for every application.

The housing, with minimalist and elegant lines, is made of Polypropylene with UV-resistant treatment; this ensures robustness and greater durability to exposure to sun, moisture and rain. Plastic woofer, Mylar tweeter and plastic cover of rear connections make these speakers completely waterproof. Both transducers are selected to offer not only waterproofness and high durability, but also an excellent level of audio quality. The buit-in line transformer allows the speaker to be adapted to both constant-voltage - with 4 selectable power levels - and low-impedance systems.

Each Liveo series speaker, in order to simplify installation as much as possible, comes with both a "C" bracket and a "ball-shaped" bracket, both with adjustable horizontal and vertical positions.

















PRODUCT DETAILS

Key features

| 2-Way Passive with 30W RMS Power | |
|----------------------------------------------------------------------|--|
| IP65 Protection Rating for Outdoor/Indoor Applications | |
| Available in Black or White Finish | |
| UV-Resistant PP Housing | |
| Built-in 70V/100V Line Transformer | |
| Power Tap Selector for 70/100V or low-impedance systems | |
| Horizontal and Vertical adjustable C-Bracket and Ball-Shaped bracket | |
| Security Wire included | |
| Paintable Housing and Grille | |



Specifications

| Speaker Type | 2-Way Passive |
|--------------------------------------------------|----------------------------------------------------------------------------------------------|
| IP Rating | IP65 |
| RMS Power (@ 8ohm) | 30W |
| Program Power (@ 8ohm) | 60W |
| Frequency Response (-10dB) | 60Hz-20kHz |
| Sensitivity (1w@1m) | 85dB |
| Impedance | 8ohm |
| Woofer | 5.25" (135mm), PP cone |
| Tweeter | 0.5" (13mm), Mylar dome |
| Crossover Frequency | 3.5kHz |
| 70/100V Line Transformer with Power Tap Selector | (100V) 16W, 8W, 4W, 2W - (70V) 8W, 4W, 2W, 1W - 8Ω |
| Housing | UV-Resistant PP, paintable |
| Bracket | C-Bracket and Ball-shaped Bracket with Pan/Tilt adjustable angles and stainless-steel screws |
| Grille | Perforated aluminum, powder coated paint, acoustic transparent, paintable |
| Color | Black |
| Product Size - no bracket included (WxDxH) | 156 x 156 x 227 mm (6.1 x 6.1 x 8.9 inch) |
| Speaker Weight (single unit, no bracket) | 1.5kg - 3.3 lbs. |
| Packing Size (WxDxH) (pair) | 420 x 195 x 255 mm (16.5 x 7.7 x 10.0 inch) |
| Packing Weight (pair) | 3.9kg - 8.6 lbs. |