

HMIX-622

1U Rack 8-Input Stereo Mixer

The HMIX-622 is designed for Commercial Audio applications where many microphone or line inputs are required. The Mic/Line section consists of 6 combo inputs (XLR + ¼" Jack) with level control, Mic/Line selector and Phantom power in case of condenser microphones. Channel 1 also has Priority function with adjustable threshold. The Aux section provides 2 stereo RCA inputs, also with independent level, and a stereo line output with RCA connectors for recording or connecting to other devices. Finally, the master section has stereo output with balanced XLR connectors, mono output with ¼" jack connector, volume control and front stereo VU meter. The mixer accepts DC24V auxiliary power for emergency systems.



PRODUCT DETAILS

Key features

6 Mic/Line inputs

+48V phantom power supply

Priority function (on channel 1) with adjustable threshold

2 Stereo Line Inputs

Stereo Balanced Outputs

Small size in 1 rack unit

DC24V auxiliary power input

Specifications

Mic/Line Inputs	6x Balanced XLR / 1/4" Combo connectors
Aux Inputs	2x L+R RCA
Outputs	L+R male XLR, 1/4" Jack, L+R RCA (Line Out)
Controls	6x Mic/Line level, 2x Aux level, Treble (High), Bass (Low), Master
Input Impedance	3.3k Ohms (mic/line), 10k Ohms (aux)
Mic Frequency Response	20Hz - 18kHz
Line Frequency Response	14Hz - 20kHz
Aux Frequency Response	10Hz - 23kHz
Mic Input Sensitivity	-45dBV
Aux/Line Input Sensitivity	-10dBV
Mic S/N Ratio	55dB
Aux/Line S/N Ratio	60dB
THD	0.05%
Power Supply	100-240Vac 50/60Hz (IEC) or 24VDC (terminals)
Fuse	T1AL 250V (mains) or F500mA (24DC)
Phantom Power	+48V (switchable)
Product Size (WxDxH)	482 x 132 x 45 mm (18.9 x 5.2 x 1.7 in.)
Product Weight	1.7 kg (3.75 lbs.)
Carton Size	565 x 210 x 74 mm (22.2 x 8.3 x 2.9 in.)
Carton Weight	1.9 kg (4,19 lbs.)